

# XT30-SERIES CONTRACTOR SUCTION HOSE



*Turboflex® XT30-Series Contractors Suction Hoses are designed to provide flexibility in pumping and dewatering applications. Suitable for suction and discharge duty this premium water hose is designed for efficient transfer of non-abrasive materials, such as air and water.*

*Commonly used in pump hire applications, soft cuffed ends make easy installation of hose tails and couplings. As standard these hoses come in 3m and 6m lengths, however being an Australian manufacturer, we can custom make to any length required.*



## TECHNICAL SPECIFICATIONS

Hose size	DN80 – 300
Length	3mt, 6mt
Pressure rating	-100kPa - +1000kPa
End connections	Cuffed Fitted with M/F Bauer couplings Custom
Optional extras	ID tagging

## MATERIAL SPECIFICATIONS

Inner Liner	NR/SBR blend
Reinforcement	Spiralled synthetic fabric Wire helix
Outer cover	NR/SBR blend

## TECHNICAL PROPERTIES

HOSE SIZE		STANDARD LINER THICKNESS	VACUUM RATING	STANDARD WORKING PRESSURE		SAFETY FACTOR	WEIGHT	MINIMUM BEND RADIUS
DN	mm	mm	%	kPa	PSI	Ratio	Kg/mt	X Dia
80	76.2	3	100	1000	145	4:1	4	4
100	101.6	3	100	1000	145	4:1	5	4
125	127	3	100	1000	145	4:1	6	4
150	152.4	3	100	1000	145	4:1	7	4
200	203.2	3	100	1000	145	4:1	12	4
250	254	3	100	1000	145	4:1	17	4
300	304.8	3	100	1000	145	4:1	25	4